




Richpeace®
A Member of SGGroup

Richpeace Automatic Mask Bagging Machine II



Application:

Suitable for automatic bagging operations for various types of mask.

Main functions and features:

1. Three-servo motor control system, can automatically set the bag length (within 400mm) to achieve specified length of the auto-packing. Including empty packing detection, through the checking of product' s origin, auto automatically identify the material position, machine will be stopped when the feeding material is not there, and started when there is product material coming in.
2. Human-machine interactive interface, convenient and fast to set parameters, can store products parameters for various products specification, allow to choose parameters according to product spec.
3. Self-diagnostic function, clear fault and reset in one-step.
4. High-sensitivity photoelectric sensor mark tracking, digitally input seal and cut position, making the position more accurate.
5. Independent PID control of temperature, suitable for various packing material.
6. Positioning stop function, material not sticking on the cutter, no wastage of packing film.
7. Simple and easy of the transmission system, reliable and preventative maintenance easily.
8. All controls are performing by program, convenient on features tuning and technologies upgrade, fulfill intelligent operation.

Suitable material:

Heat-sealed film PVC, BOPP, OPP, CPP, Metalized PET foil, aluminum-plastic foil, paper film, paper plastic and other single-layer or multi-layers heat-sealed degradable material, etc.

Main Parameters & Main Configuration:

Main Parameters		Main Configuration	
Model	RPAP-FM-F-2-100x250-HM-BSP-CRF-P-1P220 (II)	Touch screen	YUNKONG
Length of Packaging Bags	60mm-500mm	Servor Motor	YUNKONG
Width of Packaging Bags	35mm-160mm	Servor controller	YUNKONG
Product Height	5mm-60mm	Proximity switch	HONEYWELL
Film length	90mm-400mm	Photoelectric switch	OETAI
Film roll diameter	Max. 350mm	Temperature controller	KEYANG
Package speed	35-160 bags/min (support 1-20 pcs/bag)	Solid state relay	AICO
Power supply	220V, 50Hz, 3.1kW	Switching power supply	SCHNEIDER
Machine dimension	4230mm×750mm×1075mm	Optional Equipments	
Machine weight	350kg	1. Special sealing method (straight grain) 2. All stainless steel (host base) 3. Coder (production date) 4. Exhaust device	

TIANJIN RICHPEACE AI CO., LIMITED

Add: No.6 Baozhong Road,
Baodi Economic Development Zone,
Tianjin City, 301800 China

Tel: +86-22-22533456
Fax: +86-22-22530075
Email: sales@richpeace.com

